

Wild Boys + female vox Technical Rider for overseas, April 2016

Telephone Steve on +44 (0)7776 127 468 with any queries.

If any of the items listed are not available and substitutions need to be made please clear with the band.

MAINS POWER SUPPLY IMPORTANT:

**CHECK MAINS VOLTAGE/FREQUENCY SUPPLY PROVIDED MATCHES ALL EQUIPMENT PROVIDED
PLEASE ALSO INFORM OF THE MAINS VOLTAGE & FREQUENCY BEING PROVIDED AND SPECIFY THE MAINS
CONNECTOR TYPE, *i.e. European schuko, 230vac 50Hz, USA Nema mains plug, 120vac 60Hz, etc***

CLIENT TO SUPPLY:

Front of house & Monitoring (PA-system)

- 2 x Radio mic's- Sennheiser G3 Mic or Beta SM 58a for both Main vocals
- 1 x SM 58 for guitarist vocals (beta version preferred) Radio mic acceptable.
- 1 x mic for electric guitar amp (*NOTE: it is likely that the guitar-signal will be delivered as an XLR DI/speaker-emulated output located at the guitarists feet so please allow a long enough XLR cable*)
- Full microphone set suited the drum kit provided (*see drummer's rider below*)
- 3 x Quality IEM systems (vocalists x2 + guitarist) to be provided and in tested working condition. All systems to include wireless transmitters and belt packs with single 1/8" stereo jack out put. Devices must include optional volume-limiters (band will supply their own ear pieces)
- Sufficient spare batteries for all wireless units
- A small mixer with headphone out (for Drummer's in ear feed) minimum 4 channel. (ensure headphone output can supply 1/8" stereo jack)
- A Full-range front of house system consisting of power amps + speakers or active/powered units (bi/tri-amped) suited to the size of the venue.
- Yamaha LS9 16 channel mixing console (32 channel version acceptable) only if the band are operating the desk themselves otherwise a similar or better unit that the supplied sound-engineer prefers or personally specifies. (*see crew notes below*)
- Boom/angled microphone stands for all microphones listed or appropriate mountings for mics (ie drums mics)

Crew and personnel

- Unless the band have specified otherwise, it is expected that a sound-engineer (and lighting-engineer) be provided to support the band as part of the PA, stage and lighting provisions.
- Whether or not a crew and technical staff are provided, it will be expected that all equipment will be set-up and ready to use, including the stage, sound-system, lights and monitoring, etc.

Main vocalists (male + female)

- Vocal equipment listed in "PA-system, above" (wireless mics and radio-in-ear systems)
- Straight microphone stands for BOTH main vocalists

Guitarist (with vocals)

- Vocal equipment listed in "PA-system, above" (mics and radio-in-ear systems)
- Primary monitor: radio-in-ear system. Additionally monitoring by floor-wedge
- Boom/angled microphone stands for vocals
- Half-stack or combo with minimum of 3 foot-switchable channels (clean/crunch/lead/etc) Min 50w
- Quality mono 1/4" Jack-to-jack cables of 6 metres minimum length x4

Bassist

- Bass Amplifier - Preferably either a 2 x 10" or 1 x 15" combo amp or 4 x 10" speaker cab with suitable Bass amplifier head. Anything by Ampeg, EBS, MarkBass, Gallien Krueger
- Quality mono 1/4" Jack-to-jack cables of 6 metres minimum length x4
- Monitoring by floor-wedge

Keyboardist

- Roland RD800 stage piano
- Monitoring by floor-wedge
- 1 dual- tier adjustable-height keyboard stand- Upper tier no wider than 1 metre to accommodate small-keyboard or laptop table
bottom tier to accommodate the Roland RD800
- 2 long x mono jack to male XLR (balanced)
- 1 x long XLR (min 6 metres)
- 2 x long midi cable (min 6 metres)
- 2 x 4 way power extensions with long leads.

Drummer

- DI box with “thru” for Backing track (Band will provide backing ipad as playback device)
- ¼” stereo to 2x mono jacks (for the ipad output)
LEFT OUT=click to drummers mixer, RIGHT OUT=split feed to drummers-mixer and FOH *via DI box*
- Table or music stand for the ipad- positioned for drummer’s easy access
- Monitor by way of an ear-ear feed (XLR to drummers own mixing desk) and optional floor-wedge

Drum kit:

- 22" kick/bass drum x1
- 14" snare drum x1
- 13" rack tom
- 16" floor tom
- Preferably branded drums "DW, Tama,pearl,Yamaha"

Cymbals:

- Hi-hats 14" x1
- Crash cymbals x2 17" & 19 "
- Ride cymbal 20-22" x1

hardware

- Appropriate hardware for all drums and cymbals
- 1 hi hat stand with clutch
- 2 crash Stands
- 1 ride cymbal stand with boom arm.
- 1 bass drum pedal (preferably tama iron cobra single pedal) + a spare/back-up
- 1 snare stand
- Tom mounts and floor tom legs.
- 1 drum stool
- 1 drum mat

General equipment

- Quality XLR cables of appropriate length for all microphones listed
- Appropriate cables to connect all items to the main mixing console (including: FOH system, monitors and equipment used by all performers-*see each members list*)
- Mains power cables for all equipment listed
- Adequate power outlets and/or extension leads for all equipment listed

A safe and “clean” reliable power supply for all equipment listed

OTHER:

Staging & lighting:

Minimum stage size 7m wide x 5m deep. Drum Riser 600mm high 3m wide x 2.5m deep. The stage should be sturdy and level the carpet should be securely fitted.

Lighting suitable for the venue with operative or complete automation. Performers will not be able to control the lighting.

